


MATERIAL LIST OF MODEL : MR-21

NO.	PART NAME	MATERIAL
1	Actuator	Nylon 66
2	Base	Nylon 66
3	Contact	Silver Alloy
4	Moving Contact	Silver Plated Phosphor Bronze
5	Center Terminal	Tin Plated Copper
6	Stationary Contact Terminal	Tin Plated Copper

solteam
文件管制
發行章
JAN. 10. 2006

NO.	DATE	REVISION DESCRIPTION	ISSUE	REVISE	APPROVED
8					
7					
6	060106	MODIFY SPEC.	A6		李碩


崧騰企業股份有限公司 SOLTEAM ELECTRONICS CO.,LTD


核准 APPROVED BY	李碩	日期 DATE	060106	投影法		單位 DIMENSION UNIT	mm
校對 CHECKED BY	李碩	日期 DATE	060106	比例 SCALE	2 : 1	機型 PART NAME	ROCKER SWITCH
繪圖 DRAWN BY	溫小姐	日期 DATE	970722	路徑 DWG NO	E:\成品圖\MR-21\	型號 PART NO	MR-21N-2BB-F2


⑥ ROCKER SWITCHES MODEL : MR-21 SERIES

CONTACT RATING : 10A 125VAC 5A 250VAC (UL)
10A 125VAC 7A 250VAC (CSA)
6A 250VAC~ μT85 (ⒹⓈⓃⒻⅠ, VDE)

UL CERTIFICATE NO.:E148157
CSA CERTIFICATE NO.:077849_0_000
NEMKO CERTIFICATE NO.:P05204695
DEMKO CERTIFICATE NO.:313488_01
SEMKO CERTIFICATE NO.:509266
FI CERTIFICATE NO.:FI22044
③ VDE CERTIFICATE NO.:115442
CONTACT RESISTANCE : 20mΩ(MAX).INITIAL
INSULATION RESISTANCE : 500MΩ(MIN). 500VDC
INITIAL WITHSTAND VOLTAGE:
PLEASE REFERENCE TEST SPECIFICATION-3.3
LIFE CYCLES : OVER 10,000 CYCLES
OPERATING FORCE : 650±150 GRAM
MATERIAL USED MUST BE COMPLY WITH BQI-0555 .







solteam
文件管制
發行章
JAN. 10. 2006

Panel Thickness	Dim.x	Dim.Y
0.75–1.25	19.2/19.1	13.0/12.9
1.25–2.0	19.4/19.3	13.0/12.9
2.0 –3.0	19.8/19.7	13.0/12.9

TOLERANCES UNLESS OTHERWISE 未指定容許差尺寸之公差	
BASIC DIMENSIONS TOLERANCES	
UP TO 10 (10 以下)	±0.3
ABOVE 10 TO 100(10~100)	±0.5
ABOVE 100 (100 以上)	±0.8
ANGULAR DIMENSIONS(角度)	±5°

NO.	DATE	REVISION DESCRIPTION	ISSUE	REVISE	APPROVED
⑧					
⑦					
⑥	060106	NODIFY SPEC.	A6	溫小燕	李碩

崧騰企業股份有限公司 SOLTEAM ELECTRONICS CO.,LTD

核准 APPROVED BY	李碩	日期 DATE	06/01/06	投影法		單位	DIMENSION UNIT	mm	
校對 CHECKED BY	李碩	日期 DATE	06/01/06	比例 SCALE	1.5 : 1	機型 PART NAME	ROCKER SWITCH		
繪圖 DRAWN BY	溫小燕	日期 DATE	970801	路徑 DWG NO	E:\成品圖\MR-21\	型號 PART NO	MR-21N-2BB-F2		